

Bonethane & The Bonethane SplashbackTM

CARE SHEET

The **BonethaneTM** product is made of solid polymer material and coating formulae. Due to the exceptional weathering and impact characteristics of BonethaneTM the variety of use for internal and external applications are endless.

BonethaneTM offers an easy-to-care-for-surface. When cleaning BonethaneTM it is strictly advised to wash BonethaneTM with **WARM SOAPY (ie detergent) WATER or COMMERCIAL PLASTIC CLEANER** and soft polish cloth to achieve pure radiance and shine.

With all plastic compounds harsh cleaning agents can only discolour over time.

CARE DO'S

- To clean: Strictly use warm soaked soapy sponge in circular motion
- To rinse: soft toweling cloth merge into clean warm water & squeeze, wiping soap off in down motion. Repeat second or third time, removing excess lather.
- To dry: DO NOT POLISH. BonethaneTM will dry shiny, providing the excess water becomes minimal when wiping down with warm damp toweling cloth, allowing to dry with shine.
- Scratches can be buffed using same application as you would a vehicle(fine grade car polish with no cleaning agents. Visit www.bonethane.com for further technical detail.

CARE DON'Ts

Do not use abrasive cleaners, scourers or scouring compounds, window cleaners, acetone, toluene chloroform, xylene, amyl acetate, dichloromethane, butyl alcohol, butyl acetate, cellusolve, giacial acetate acid, cresols/phenols ,halogenated solvents, Ketone (pvc glue) ethylacetate, chlorinated solvents, Sulphuric acid, MEK methyl alcohol and bleach. Do not apply thinners to the face of BonethaneTM. No Silicone based products to the face. Not a bench top. Do not place directly against or on exposed flames or heat expelled elements of extreme heat.

DO NOT

Do not leave very hot items ie: hot pans, hot jugs leaning against BonethaneTM. This could damage or mark the product. Do not place BonethaneTM on a direct flame, heat element or anything of constant extreme heat nature (a distance minimum of 20cm) or what appears in care don'ts, as this requires a metal, glass or mosaic tile strip. BonethaneTM has a continuous service temperature of 100°. Warranty will be void if information stated on these product sheets are not strictly followed. BonethaneTM must sit up right against wall, minimum of 12cm from any heat expelled appliance. Items of extreme heat nature must not touch or be placed too close to BonethaneTM.

Application Benefits

- High Impact Resistance
 - Flexibility
 - Durability
 - Weather Resistant, Water resistant, water will not penetrate coating formulae.
- BonethaneTM Wall panelling for outside use, is UV Coated. Bonethane GN is Bendable for more information contact Bonethane on 0297562880 or vist website www.bonethane.com

Available in 3 grades Bonethane Premium, Bonethane GN & Bonethane UV choice of single colour or combination colour (special effects) in gloss like glass finish or velvet finish, all customised to your individual look.

If you have further enquires please call **02 9756 2880** or visit www.bonethane.com